

Confidential price list effective 1 May 2009. Prices are subject to change without notice. All RRP prices include GST.

Model/Code	Description	RRP
<b>High End Series</b>		
ULT-Edition 8	<b>Edition 8</b> - Hand made in Germany these headphones incorporate stunning attention to detail. Premium quality materials, including Ruthenium and Ethiopian sheepskin leather are brought together in this exceptional product.	2,798.00
ULT-101-H-Amp	High Quality Headphone Amplifier perfect for use with the Edition 8 Series	2,595.00
<b>Professional Series</b>		
ULT-P550	<b>Proline 550</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound. Technical specifications: Frequency range 10-22.000 Hz, Impedance 64 Ohm, Sound pressure level 102 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE (=Ultra Low Emission) standard, Driver 50 mm Mylar, Weight 295 g (without cord). <i>Includes Carry Case.</i>	455.00
ULT-P650	<b>Proline 650</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound. Technical specifications: Frequency range 10-25.000 Hz, Impedance 75 Ohm, Sound pressure level 95 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 40 mm gold-plated, Weight 295 g (without cord). <i>Includes Carry Case.</i>	562.00
ULT-P750	<b>Proline 750</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound. Technical specifications: Frequency range 8-35.000 Hz, Impedance 40 Ohm, Sound pressure level 94 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 40 mm titanium-plated, Weight 295 g (without cord). <i>Includes Carry Case.</i>	695.00
ULT-P900	<b>Proline 900</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound. Technical specifications: Frequency range 6-42,000 Hz, Impedance 40 Ohm, Sound pressure level 96 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 40 mm titanium-plated, Weight 295 g (without cord). <i>Includes Carry Case.</i>	890.00
ULT-P900BAL	<b>Proline 900-Balanced</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound. Technical specifications: Frequency range 6-42,000 Hz, Impedance 40 Ohm, Sound pressure level 96 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 40 mm titanium-plated, Weight 295 g (without cord). <i>Includes Carry Case.</i>	1,375.00
ULT-P2500	<b>Proline 2500</b> - Foldable, open-back professional headphones with S-Logic™ Natural Surround Sound, Dynamic principle. Technical specifications: Frequency range 8-35.000 Hz, Impedance 40 Ohm, Sound pressure level 94 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 40 mm titanium-plated, Weight 292 g (without cord). <i>Includes Carry Case.</i>	695.00
<b>DJ Series</b>		
ULT-DJ1	<b>DJ1</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound. Technical specifications: Reduced magnetic field emissions LE standard (LE= Low Emission), Dynamic principle, Frequency range 10 Hz - 22.000 Hz, Impedance 64 Ohm, Sound pressure level 103 dB, Driver 50 mm Mylar, Coiled cord: length > 3m, 3,5/6,3 mm gold-plated plug, Weight LE 265 g (without cord). <i>Revised Aluminium Name Plate and thicker Headpads.</i>	365.00
ULT-DJ1-P	<b>DJ1 Pro</b> - Foldable, closed-back professional headphones with S-Logic™ Natural Surround Sound, MU Metal shielding Safer hearing. Technical specifications: S-Logic™ Natural Surround Sound, Dynamic principle, Frequency range 10-22.000 Hz, Impedance 64 Ohm, Sound pressure level 102 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 50 mm Mylar, Weight 295 g (without cord). <i>Revised Aluminium Name Plate and thicker Headpads. Supplied with Hard Carry Case, spare Headpads, 3m Straight and 3m Curly Connecting Cables.</i>	455.00

Confidential price list effective 1 May 2009. Prices are subject to change without notice. All RRP prices include GST.

Model/Code	Description	RRP
<b>Hifi Line Series</b>		
ULT-H15G	<b>HFI 15G</b> - Open, supra-aural superior headphones with S-Logic™ Natural Surround Sound. Technical specifications: S-Logic™ Natural Surround Sound, Reduced magnetic field emissions Standard LE (=Low Emission), Dynamic principle, Frequency range 20 Hz - 20.000 Hz, Impedance 32 Ohm, Sound pressure level 96 dB, Driver 40 mm Mylar, Weight 85 g (without cord), Cord length ca. 3 m, 3.5/6.3mm gold-plated plug . <i>Discontinued Model, limited stock remaining.</i>	239.00
ULT-H450	<b>HFI 450 - NEW 2008 MODEL</b> - Closed-back superior headphones with S-Logic™ Natural Surround Sound. Technical specifications: 20-20.000 Hz, 40mm Mylar Driver, 32 Ohm impedance, Sound pressure level 96 dB, weight 265g, cord length 3m.	275.00
ULT-H550	<b>HFI 550</b> - Foldable, closed-back superior headphones with S-Logic™ Natural Surround Sound. Technical specifications: S-Logic™ Natural Surround Sound System, Reduced magnetic field emissions Standard LE (= Low Emission), Dynamic principle, Frequency range 10-22.000 Hz, Impedance 64 Ohm, Sound pressure level 100 dB, Driver 50 mm Mylar, Cord length ca. 3 m, 3.5/6.3mm gold-plated plug, Weight 265 g (without cord). <i>Discontinued Model, limited stock remaining.</i>	295.00
ULT-H580	<b>HFI 580 - NEW 2008 MODEL</b> - Foldable, closed-back superior headphones with S-Logic™ Plus - Enhanced Natural Surround Sound. New Standard MU Metal Shielding - Enhanced reduction in magnetic field emissions. Technical specifications: Dynamic principle, Frequency range 10-22.000 Hz, Impedance 64 Ohm, Sound pressure level 101 dB, Driver 50 mm Mylar, Cord length 3m, 3.5/6.3mm gold-plated plug, Weight 285 g (without cord).	367.00
ULT-H680	<b>HFI 680 - NEW 2008 MODEL</b> - Foldable, closed-back superior headphones with S-Logic™ Plus - Enhanced Natural Surround Sound. New Standard MU Metal Shielding - Enhanced reduction in magnetic field emissions. Technical specifications: Dynamic principle, Frequency range 15-25.000 Hz, Impedance 75 Ohm, Sound pressure level 99 dB, Driver 40 mm Mylar/Gold, Cord length 3m, 3.5/6.3mm gold-plated plug, Weight 285 g (without cord).	455.00
ULT-H780	<b>HFI 780 - NEW 2008 MODEL</b> - Foldable, closed-back superior headphones with S-Logic™ Plus - Enhanced Natural Surround Sound. New Standard MU Metal Shielding - Enhanced reduction in magnetic field emissions. Technical specifications: Dynamic principle, Frequency range 10-26.000 Hz, Impedance 35 Ohm, Sound pressure level 96 dB, Driver 40 mm Mylar/Gold, Cord length 3m, 3.5/6.3mm gold-plated plug, Weight 285 g (without cord).	479.00
ULT-H2200	<b>HFI 2200</b> - Foldable, open-back superior headphones with S-Logic™ Natural Surround Sound and MU Metal shielding (ULE technology). Technical specifications: S-Logic™ Natural Surround Sound, Dynamic principle, Frequency range 10 - 25.000 Hz, Impedance 75 Ohm, Sound pressure level 94 dB, MU Metal bufferboard, reduced field emissions in accordance with ULE standard, Driver 40 mm gold-plated, Weight 292 g (without cord), Detachable cable (length 3 m), Incl.adapter 3.5/6.3 mm gold-plated. <i>Special pricing on limited stock, updated model to follow shortly.</i>	547.00
<b>i-CANS</b>		
ULT-Zino	<b>Zino</b> - White. Foldable, semi-open, supra aural headphones. These headphones have been specially designed and developed for iPod, MP3 players and other portable sound devices. Equipped with S-Logic™ Natural Surround Sound and MU Metal shielding.	199.00



